

MICRO
POLYMER
TECHNOLOGIES

MPT

Hi-Mat 102A



Hi-Mat 102A is based on polyethylene wax dispersions with controlled particle sizes and distributions.

APPLICATIONS

Matting, abrasion resistance and anti-scratch agents for UV curable coatings on plastic and wood.

- mobile phone cases
- wood finish
- other decoration coatings
- inks

TYPICAL PROPERTIES

Chemical description	polyethylene wax
Appearance	liquid
Non-volatile (125°C*1hr)	10%
Specific gravity (@25°C)	0.88
Max size	15 μ m
Solvent	toluene

ADVANTAGES

Improve the following surface properties

- matting performance
- abrasion resistance
- anti-scratch
- easy dispersion

INCORPORATION

Hi-Mat 102A should be stirred uniformly before incorporation.

Hi-Mat 102A should be post added using medium speed dispersion apparatus.

* 10 ~ 35% by weight of UV coating

The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, expressed or implied, including a warranty of merchantability and fitness for use.

MPT

852-8 Osikdo-dong, Gunsan City, Jeonrabukdo, Korea [573-540]

Phone : 82-63-465-9780, Fax : 82-63-465-9789, e-mail : mpt@micropolymer.com