

MICRO
POLYMER
TECHNOLOGIES

MPT Hi-Flo 325P



Hi-Flo 325P is based on polypropylene wax, micronized and classified for textured surface in paints and coatings.

APPLICATIONS

- wood coatings
- metal coatings
- power coatings

TYPICAL PROPERTIES

Chemical description	polypropylene wax
Appearance	free-flowing white powder
Particle size	D50 10 ~ 14 μ m
	D98 40 μ m under
Specific gravity (@25 $^{\circ}$ C	0.89

ADVANTAGES

Improve the following surface properties

- matting performance
- abrasion resistance
- anti-scratch
- easy dispersion

INCORPORATION

Hi-Flo 325P can be incorporated easily into the coating using stirrers or dissolvers.

* Between 1.0 and 5.0%, based on total formulation weight.

The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, expressed or implied, including a warranty of merchantability and fitness for use.

MPT

852-8 Osikdo-dong, Gunsan City, Jeonrabukdo, Korea [573-540]

Phone : 82-63-465-9780, Fax : 82-63-465-9789, e-mail : mpt@micropolymer.com