

MICRO  
POLYMER  
TECHNOLOGIES

MPT

Hi-Thix 600BA



Haps free, Hi-Thix 600BA is thixotropic agent in paste form consisting of specially prepared polyamide wax swollen/dispersed in butyl acetate and alcohol. This product is formulated intricately in order to give anti-sagging property.

## APPLICATIONS

Hi-Thix 600BA is recommended for plastic and wood coating.

## TYPICAL PROPERTIES

Chemical description .....	Polyamide wax
Appearance .....	Paste
Non-volatile (125 °C*1hr) .....	20%
Specific gravity (@25 °C) .....	0.89
Solvent .....	Butyl acetate, alcohol

## ADVANTAGES

- Anti-sagging / anti-settling
- Very good flow and leveling
- Tolerates high processing temperatures
- Applicable to wide range of plastic and wood coatings

## INCORPORATION

Hi-Thix 600BA is pastes of activated particles in haps free solvents for medium viscosity paints such as plastic and wood coating and medium speed disperser is necessary.

- \* Anti-sagging application : 2.0 ~ 5.0% by weight of paint
- \* Anti-Settling application : 1.0 ~ 2.0% by weight of paint

The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, expressed or implied, including a warranty of merchantability and fitness for use.

**MPT**

852-8 Osikdo-dong, Gunsan City, Jeonrabukdo, Korea [573-540]

Phone : 82-63-465-9780, Fax : 82-63-465-9789, e-mail : mpt@micropolymer.com