

MICRO  
POLYMER  
TECHNOLOGIES

MPT

Hi-Thix 602



Hi-Thix 602 is thixotropic agent in paste form consisting of specially prepared polyamide wax swollen/dispersed in solvents. This product is formulated intricately in order to give a very strong anti-sagging property.

## APPLICATIONS

Hi-Thix 602 is recommended for solvent based heavy duty coating; epoxy primers, chlorinated rubber primers and alkyd primers.

## TYPICAL PROPERTIES

Chemical description .....	Polyamide wax
Appearance .....	Paste
Non-volatile (125°C*1hr) .....	20%
Specific gravity (@25°C) .....	0.89
Solvent .....	Xylene, alcohol

## ADVANTAGES

- Very Strong anti-sagging / anti-settling
- Very good flow and leveling
- Tolerates high processing temperatures
- Applicable to wide range of solvent based coatings

## INCORPORATION

Hi-Thix 602 is pastes of activated particles in solvents for high viscosity paints such as heavy duty coatings and sand mill is necessary.

- \* Anti-sagging application : 2.0 ~ 5.0% by weight of paint
- \* Anti-Settling application : 1.0 ~ 2.0% by weight of paint

The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, expressed or implied, including a warranty of merchantability and fitness for use.

**MPT**

852-8 Osikdo-dong, Gunsan City, Jeonrabukdo, Korea [573-540]

Phone : 82-63-465-9780, Fax : 82-63-465-9789, e-mail : mpt@micropolymer.com