

MICRO
POLYMER
TECHNOLOGIES

MPT

PO-202



PO-202 is dispersion of EAA copolymer wax in xylene, butyl acetate and butanol
For solvent based automotive and plastic coating. This product improves the pigment
orientation effect and thus enhance the flip-flop effect. Pigment sedimentation is reduced.

APPLICATIONS

PO-202 is recommended for solvent base metallic (aluminum, mica, etc.) coating.

TYPICAL PROPERTIES

Chemical description	EAA wax
Appearance	liquid
Non-volatile (125°C*1hr)	6%
Specific gravity (@25°C)	0.88
Solvent	xylene, butyl acetate and butanol

ADVANTAGES

- improves metallic orientation (aluminum, mica, etc.)
- enhance flip-flop effect
- reduces pigment sedimentation
- reduces short wave defects (mottling, etc.)
- easy dispersion

INCORPORATION

PO-202 should be before use and incorporated prior to CAB addition, preferably via
the aluminum slurry to the binder solution under agitation.

* 10 ~ 30% by weight of solid resin

The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, expressed or implied, including a warranty of merchantability and fitness for use.

MPT

852-8 Osikdo-dong, Gunsan City, Jeonrabukdo, Korea [573-540]

Phone : 82-63-465-9780, Fax : 82-63-465-9789, e-mail : mpt@micropolymer.com